

537, 081

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number  
**WO 2004/052135 A1**

(51) International Patent Classification<sup>7</sup>: **A43B 13/18,**  
23/28

MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,  
YU, ZA, ZM, ZW.

(21) International Application Number:  
PCT/US2002/038955

(22) International Filing Date: 5 December 2002 (05.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and  
(72) Inventor: CARROLL, Lester, E. III [US/US]; 330 Fort  
Pickens Road 1D, Pensacola Beach, FL 32561 (US).


Declaration under Rule 4.17:  
— of inventorship (Rule 4.17(iv)) for US only

Published:  
— with international search report

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: SHOE PROVIDING VERTICAL/HORIZONTAL HEEL PRESSURE DIMINISHMENT



(57) Abstract: The modified oxford shoe (10) providing vertical and horizontal heel pressure diminishment including an optional means of adjusting pronation is an inventive device which diminishes pressures to the heel with a floating collar and supple counter assembly with adjusting strap, with spacing studs attached strategically to the sides of the midsole (15) to prevent exterior pressure to the heel and with a multi functioning cushion assembly coupled with adjustable underlying steel springs and resilient midsole (15) and wearing surface (17) to diminish pressure to the bottom of the heel and provide pronation adjustment if needed.

WO 2004/052135 A1